Information Retrieval and Machine Learning

Massimo Melucci

University of Padua
Department of Information Engineering
massimo.melucci@unipd.it

CIMI School in Machine Learning 2015

Information Retrieval Modeling

Towards modeling Boolean Modeling Vector Space Modeling Relevance Modeling Language Modeling Evaluation

Information Retrieval and Machine Learning

Massimo Melucci

University of Padua
Department of Information Engineering
massimo.melucci@unipd.it

CIMI School in Machine Learning 2015

Summary

Information Retrieval Modeling

Towards modeling

Boolean Modeling
Vector Space Modeling
Relevance Modeling
Language Modeling

Evaluation


Evaluation

Two general approaches to Information Retrieval (IR)

- First, theory, then experimentation.
- First, experimentation, then theory.
- Importance of observation.
- Circular path.

Real world \longrightarrow Theory \longrightarrow Model \longrightarrow Experiment

Theory and model



Model of IR

- ► A set of abstract structures (algebraic structures?) that describes documents and queries.
- ▶ It defines an operation called retrieval function that maps structures to the real field.
- It does not provide implementation details, but the retrieval function should be like

$$\sum_{\substack{\text{query and document} \\ \text{content descriptor } t}} \mathsf{weight}(t)$$

for efficiency reasons.

▶ It is based on a metaphor, that is, a figure of speech in which a word or phrase is applied to an object or action to which it is not literally applicable.

Summary

Information Retrieval Modeling

Towards modeling

Boolean Modeling

Vector Space Modeling Relevance Modeling Language Modeling

Introduction

- ▶ Most used model in early IR System (IRS).
- ► Little used in search engines.
- Little used by most end users.
- Requires interaction and expertise.
- It may be very effective.
- ► See [1], [2], [3], [7], [11], [30], [32].

Metaphor

- ► A content descriptor is a set of documents.
- Documents are set elements.
- Queries are Boolean expressions.
- Complex descriptors are Boolean expressions.
- ▶ The retrieval function maps a document to a real number.
- ▶ In most cases, the image is $\{0,1\}$ (i.e. true, false).

Cognitive overload

- Users are expected to know the Boolean logic.
- And the domain of the document collection.
- Otherwise, this model is cause of cognitive overload.
- ▶ That is, frustation. In particular:
- Confusion about which operator (i.e. AND, OR, NOT) should be used.
- No unique Boolean expression of a natural language expression.
- ► Some alleviation from (graphical) user interfaces.

Retrieved document set dimension

- ► The retrieved document set may be very large or very small. Two extreme cases:
- Null output.
- Output overload.

DNF

- ► Every Boolean expression can be translated into an equivalent Disjunctive Normal Form (DNF).
- ► Example: "(apple OR orange) AND NOT juice" becomes "(apple AND NOT juice) OR (orange AND NOT juice)".

- ► Term weights and heuristic weight functions.
- Term weight:

word x	weight $w(x)$
apple	2
orange	1
juice	3
A NID.	

Weight function for AND:

$$w(x_1\mathsf{AND}w_2) = w(x_1) + w(x_2)$$

Weight function for NOT:

$$w(\mathsf{NOT}x) = -w(x)$$

▶ Weight function for OR:

$$w(x_1 ORw_2) = \max\{w(x_1), w(x_2)\}\$$

Suppose a document is indexed by apple, orange and juice.

```
w((apple AND NOT juice) OR (orange AND NOT juice)
= \max\{w(\text{apple AND NOT juice}), w(\text{orange AND NOT juice})\}
= \max\{w(\text{apple}) + w(\text{NOT juice}), w(\text{orange}) + w(\text{NOT juice})\}
= \max\{w(\text{apple}) - w(\text{juice}), w(\text{orange}) - w(\text{juice})\}
= \max\{2 - 3, 1 - 3\}
= -1
```

Suppose a document is indexed by orange, juice but not apple.

```
w((apple AND NOT juice) OR (orange AND NOT juice)
= \max\{w(\text{apple AND NOT juice}), w(\text{orange AND NOT juice})\}
= \max\{w(\text{apple}) + w(\text{NOT juice}), w(\text{orange}) + w(\text{NOT juice})\}
= \max\{w(\text{apple}) - w(\text{juice}), w(\text{orange}) - w(\text{juice})\}
= \max\{0 - 3, 1 - 3\}
= -2
```

Suppose a document is indexed by orange and but not juice.

```
w((apple AND NOT juice) OR (orange AND NOT juice)
= \max\{w(\text{apple AND NOT juice}), w(\text{orange AND NOT juice})\}
= \max\{w(\text{apple}) + w(\text{NOT juice}), w(\text{orange}) + w(\text{NOT juice})\}
= \max\{w(\text{apple}) - w(\text{juice}), w(\text{orange}) - w(\text{juice})\}
= \max\{2 - 0, 1 - 0\}
= 2
```

Summary

Information Retrieval Modeling

Boolean Modeling

Vector Space Modeling

Relevance Modeling
Language Modeling
Evaluation

Vector-space modeling

- ► The early formulation by Gerald Salton was in the 1960s.
- It became well known in the 1970s.
- ▶ It was applied to several tasks in the 1980s
- and industrialized in the 1990s.
- Its name is Vector Space Model (VSM).
- See [12], [17], [18], [19], [20], [21], [22], [23], [24], [25], [26], [27].


VSM made simple

- Documents and queries are vectors.
- Documents are ranked by inner product.
- \blacktriangleright Example: two document vectors x_1, x_2 and one query vector y:

$$x_1 = \begin{pmatrix} 1 \\ 0 \\ 2 \end{pmatrix} \qquad x_1 = \begin{pmatrix} 0 \\ 1 \\ -1 \end{pmatrix} \qquad y = \begin{pmatrix} 1 \\ 1 \\ 1 \end{pmatrix}$$
$$x_1^* y = 3 \qquad x_2^* y = 0$$

Massimo Melucci/20/ME School, 2015


Graphically:



What are vectors?


- A content descriptor is a basis vector.
- ▶ An index is a basis of a real vector space.
- ► The number of distinct descriptors is the dimension of the space.
- Documents are vectors.
- Queries are vectors.
- Complex descriptors are vectors.
- Passages are vectors.
- ▶ ..
- ► The retrieval function maps a document-query to a real number.

Searching in the two-dimensional space




- \triangleright start from (0,0) without terms in mind
- ightharpoonup choose ${
 m t}_1$ with weight c_1
- the query is $c_1 t_1$
- ► choose t₂ with weight c₂
- the query/document is $c_1t_1 + c_2t_2$

Searching in the three-dimensional space



- ightharpoonup start from (0,0) without terms in mind
- ightharpoonup choose t_1 with weight c_1
- ► choose t₂ with weight c₂
- ► choose t₃ with weight c₃
- the query/document is $c_1t_1 + c_2t_2 + c_3t_3$

Searching in the three-dimensional multimedia space



- ▶ start from (0,0) without descriptors in mind
- choose video genre with weight c_{video}
- ightharpoonup choose music timbre $_2$ with weight c_{timbre}
- choose color with weight c_{color}
- ▶ the query/document is c_{video}video genre + c_{timbre}music timbre + c_{color}color

Vector space concepts

- Linear independence.
- Vector basis.
- Inner product.
- Orthogonality.
- Orthonormality.

Linear independence

▶ Let

$$T = \{\mathbf{t}_1, \ldots, \mathbf{t}_k\}$$

be a set of vectors of \mathbb{R}^n .

- T is linearly independent when any t cannot be linear combination of the other t's.
- lacktriangle For any vector x of the k-dimensional space spanned by T

$$\mathbf{x} = \sum_{i=1}^{k} c_i \mathbf{t}_i$$

- T represents an index.
- T includes one t_i for each index term.
- ► Linear independence means that no index term can be expressed as "linear combination" of other index terms.
- ▶ A basis vector of *T* is often a canonical vector and *T* becomes

$$\{(1,0,\ldots,0),(0,1,\ldots,0)\ldots,(0,0,\ldots,1)\}$$

Inner product

- \blacktriangleright Given two vectors x,y of the same vector space.
- ► The inner product is the real number

$$\mathbf{x}^*\mathbf{y} = \sum_{j=1}^n x_j y_j$$

where x^* is a row vector.

Relevant concepts

- Weighting schemes.
- Normalization schemes.
- Correlation.
- Cluster hypothesis.

Weighting schemes

- A set of rules that compute the c_{ij} 's for each document i and term j.
- Binary.

$$c_{ij} = egin{cases} 1 & ext{if } t_j ext{ occurs in } i \ 0 & ext{otherwise} \end{cases}$$

► Term Frequency (TF).

$$c_{ij} = f_{ij}$$
 f_{ij} is the frequency of term j in document i

Inverse Document Frequency (IDF).

$$c_{ij} = \log N/n_j$$
 n_j is the number of documents indexed by term j

► TF × IDF (TFIDF).

$$c_{ij} = f_{ij} \log \frac{N}{n_j}$$

Normalization schemes

- Short documents contain little data.
- Long documents contain much data.
- Short documents might containt little both relevant and non-relevant information.
- Long documents might containt much both relevant and non-relevant information.
- Normalization keeps control of document length.
- ► Three methods:
- ▶ Cosine: normalize by $\sqrt{x^*xy^*y}$ (the result is the cosine of the angle between x, y.
- ▶ Maximum weight: normalize by $\max_i x_i$.
- ▶ Pivot: normalize by smoothed document length when this length is relatively large.

Correlation

- ► Let x, y be two vectors
- Inner product

$$\mathbf{x}^*\mathbf{y} = \sum_{i=1}^k \sum_{j=1}^k c_i b_j \mathbf{t}_i \mathbf{t}_j$$

- Correlation matrix $T^*T = R = (t_i t_j)$
- Suppose that

$$R = \begin{pmatrix} 1 & 0 & \frac{1}{2} & 0 \\ 0 & 1 & 0 & 0 \\ \frac{1}{2} & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \qquad c_1 = \begin{pmatrix} 1 \\ 1 \\ 1 \\ 0 \end{pmatrix} \qquad c_2 = \begin{pmatrix} 0 \\ 0 \\ 1 \\ 1 \end{pmatrix}$$

▶ We have that

$$c_1^* R c_2 = \frac{3}{2}$$

while

$$c_1^*c_2 = 1$$

Cluster Hypothesis

- Relevant documents tend to resemble relevant documents more than non-relevant documents.
- Cluster Hypothesis "holds":
- Cluster Hypothesis "does not hold":
 - 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
- Why is the cluster hypothesis important?
- Efficiency reasons.
- Effectiveness reasons.


VSM-Relevance Feedback (RF)

- Query y.
- ightharpoonup r relevant documents x_1, \ldots, x_r .
- ightharpoonup n-r non-relevant documents x_{r+1},\ldots,x_n .
- Modified query:

$$y' = y + \sum_{j=1}^{r} \alpha_j x_j + \sum_{h=r+1}^{n} \beta_h x_h$$
 $\alpha_j \ge 0$ $\beta_h \le 0$

- ▶ Positive RF: $\sum_{j=1}^{r} \alpha_j \mathbf{x_j}, \alpha_j \geq 0$.
- ▶ Negative RF: $\sum_{h=r+1}^{n} \beta_h \mathbf{x_h}, \beta_h \leq 0.$
- ▶ The α 's and the β 's are free parameters.

Positive and negative RF



Summary

Information Retrieval Modeling

Towards modeling Boolean Modeling Vector Space Modeling

Relevance Modeling

Language Modeling

Relevance probabilistic modeling


- One of the most successful approaches to IR.
- ► Early studies and results date back to Sixties.
- Currently, it is the foundation of IR systems.
- ▶ Integrated with Machine Learning (ML) approaches.
- ► See [4], [5], [10], [16], [15], [14], [29], [28], [31].

A few definitions of probability

- Elementary event: a single occurrence of a process or phenomenon.
- Cannot be decomposed into simpler occurrences.
- Event: a set of elementary events.
- ▶ Probability measure: a function that maps an elementary event to $[0,1] \subset \mathbb{R}$.
- Degree of belief that the elementary event occurs.

Metaphor of relevance probabilistic modeling

- ▶ Document collection as elementary event space.
- ► Terms (or descriptors) are document sets.
- Relevance is a document set A.
- A changes for each information need.
- Retrieval is decision.



Retrieval decision

- Retrieval decision is affected by uncertainty.
- Statistical decision.
- Perfect retrieval: all relevant documents and no non-relevant documents.
- ▶ Two errors.
- Retrieve non-relevant documents.
- Miss relevant documents.
- Two costs.
- False alarm.
- Loss of recall.
- ▶ Optimal retrieval: the largest number of relevant documents provided the maximum number of non-relevant documents.

Decision costs

True	Decision		
Relevance	Relevant	Non-relevant	
Relevant	c(A,A)	$c(A, \bar{A})$	
Non-relevant	$c(\bar{A},A)$	$c(ar{A},ar{A})$	

Decision risks

Risk:

$$R(A|B) = c(A, A)P(A \mid B) + c(\bar{A}, A)P(\bar{A} \mid B)$$

$$R(\bar{A}|B) = c(A, \bar{A})P(A \mid B) + c(\bar{A}, \bar{A})P(\bar{A} \mid B)$$

Decision for retrieval:

$$R(A \mid B) < R(\bar{A} \mid B)$$

If and only if:

$$P(A \mid B) > c$$
 $c = \frac{c(\bar{A}, A) - c(\bar{A}, \bar{A})}{c(\bar{A}, A) - c(\bar{A}, \bar{A}) + c(A, \bar{A}) - c(A, A)}$

Probability Ranking Principle (PRP)/1

If a reference retrieval system's response to each request is a ranking of the documents in the collection in order of decreasing probability of relevance to the user who submitted the request, where the probabilities are estimated as accurately as possible on the basis of whatever data have been made available to the system for this purpose, the overall effectiveness of the system to its user will be the best that is obtainable on the basis of those data.

Implementation of P(B|A) and $P(B|\overline{A})$

- ▶ For each $b \in B$ $P(\{b\}|A)$ and $P(\{b\}|\bar{A})$ is needed.
- \blacktriangleright Documents in B are described by k properties.
- Properties are described by a random variable X.
- Simplest approach is binary:

$$X_i(\omega) = 1$$
 term occurs in ω $\omega \in B$

Curse of dimensionality

- ► Let *B* mapped to X.
- ▶ Then $P(B|A) = P(X = x|X_A = 1)$
- and $P(B|\bar{A}) = P(X = x|X_A = 0)$.
- $As X = x is X_1 = x_1, \dots, X_k = x_k,$

$$P(X = x | X_A = 1) = P(X_1 = x_1, ..., X_k = x_k | X_A = 1)$$

▶ However, we need $O(2^k)$ estimators.

Conditional stochastic independence

Assumption:

$$P(X = x | X_A = 1) = P(X_1 = x_1 | X_A = 1) \cdots P(X_k = x_k | X_A = 1)$$

$$P(X = x | X_A = 0) = P(X_1 = x_1 | X_A = 0) \cdots P(X_k = x_k | X_A = 0)$$

Let

$$p_i = P(X_i = 1 \mid X_A = 1)$$
 $q_i = P(X_i = 1 \mid X_A = 0)$

▶ Then we have the following two likelihoods:

$$P(X = x \mid X_A = 1) = \prod_{i=1}^k p_i^{x_i} (1 - p_i)^{1 - x_i}$$

$$P(X = x \mid X_A = 0) = \prod_{i=1}^k q_i^{x_i} (1 - q_i)^{1 - x_i}$$

Retrieval decision

- The retrieval decision between relevance and non-relevance implies a hypothesis test.
- Likelihood ratio:

$$L(x) = \frac{P(X = x | X_A = 1)}{P(X = x | X_A = 0)}$$

Theorem (Neyman-Pearson's Lemma (NPL))

When performing a hypothesis test between two hypotheses (e.g. relevance vs non-relevance) then the likelihood ratio which rejects relevance in favour of non-relevance when

$$L(x) \leq \lambda$$

where

$$P(X = x | X_A = 0) = \alpha$$

is the most powerful test of size α for a given threshold λ .

Application to IR of NPL

Application to IR gives the likelihood ratio of the Binary Independence Retrieval (BIR) model:

$$L(\mathbf{x}) = \frac{P(\mathbf{X} = \mathbf{x} \mid X_A = 1)}{P(\mathbf{X} = \mathbf{x} \mid X_A = 0)} = \frac{\prod_{i=1}^k p_i^{x_i} (1 - p_i)^{1 - x_i}}{\prod_{i=1}^k q_i^{x_i} (1 - q_i)^{1 - x_i}}$$

Logarithmic transformation:

$$\ell(\mathbf{x}) = \sum_{i=1}^{k} x_i w_i + \sum_{i=1}^{k} \log \frac{1 - p_i}{1 - q_i}$$

► Term Relevance Weight (TRW):

$$w_i = \log \frac{p_i(1-q_i)}{q_i(1-p_i)}$$

What about query?

- The query is not modeled.
- Relevance is modeled.
- However, efficiency reasons requires query modeling.
- Let $Y = (Y_1, ..., Y_k)$ where $Y_i = 1$ term i occurs in the query, 0 otherwise.
- ▶ Let $Z = (Z_1, ..., Z_k)$ where $Z_i = X_i Y_i$.
- ▶ Then, rank documents by $\ell(z)$.

Parameter estimation

Contingency table:

	Α	Ā	
$X_i = 1$	r _i	$n_i - r_i$	n _i
$X_i = 0$	$R-r_i$	$N-n_i-R+r_i$	$N-n_i$
	R	N-R	N

Maximum likelihood estimators:

$$\hat{p}_i = \frac{r_i}{R}$$
 $\hat{q}_i = \frac{n_i - r_i}{N - R}$

Laplace smoothing:

$$\hat{p}_i = \frac{r_i + \frac{1}{2}}{R+1} \qquad \hat{q}_i = \frac{n_i - r_i + \frac{1}{2}}{N-R+1}$$


$$TRW = \log \frac{r_i + 0.5}{R - r_i + 0.5} - \log \frac{n_i - r_i + 0.5}{N - n_i - R + r_i + 0.5}$$

Best Match N. 25 (BM25)

$$w_{ij} = \underbrace{\frac{(k_1+1)f_{ij}(k_3+1)f_{qj}}{(k+f_{ij})(k_3+f_{qj})}}_{\text{saturation term}} \mathsf{TRW}_{ij}$$

- ► / average sample document length.
- $ightharpoonup I_i$ length of document i.
- $k = k_1((1-b) + b\frac{l_i}{l}).$
- b is a free parameter (usually 0.75).
- ▶ k_1 e k_3 are free parameters (usually, 1.2 and something betwee 7 and 1000).
- f_{ij} is frequency of j in document i.
- f_{aj} is frequency of j in the query.

Saturation



Relevance Feedback (RF)

► Start with No relevance data and rank by:

$$g^{(0)}(\mathbf{z}) = \sum_{i} z_{i} w_{i}^{(0)}$$
 $w_{i}^{(0)} = \log \frac{N - n_{i} + \frac{1}{2}}{n_{i} + \frac{1}{2}}$

► Collect some relevance data and rank at step *t* by:

$$g^{(t-1)}(\mathbf{z}) = \sum_{i} z_i w_i^{(t-1)}$$

where

$$w_i^{(t-1)} = \log \hat{p}_i^{(t-1)} + \log 1 - \hat{q}_i^{(t-1)} - \log \hat{q}_i^{(t-1)} - \log 1 - \hat{p}_i^{(t-1)}$$

$$\hat{p}_i^{(t-1)} = \frac{r_i^{(t-1)} + a^{(t-1)}}{R^{(t-1)} + b^{(t-1)}} \qquad \hat{q}_i^{(t-1)} = \frac{n_i - r_i^{(t-1)} + c^{(t-1)}}{N - R^{(t-1)} + d^{(t-1)}}$$

$$a^{(t-1)} = c^{(t-1)} = \frac{1}{2} \qquad b^{(t-1)} = d^{(t-1)} = 1$$

usually.

Summary

Information Retrieval Modeling


Towards modeling Boolean Modeling Vector Space Modeling Relevance Modeling

Language Modeling

Evaluation

Metaphor

- Author thinks about queries for his document.
- ▶ He writes the document using queries and variations of them.
- Pictorially,



► See [13], [34], [35], [9], [6], [8], [33].

Assumptions

- ► The user is assumed to have a good idea of what he is searching.
- ▶ The author is assumed to have a good idea of the user's need.
- ▶ Both are assumed to use an effective and the same language.
- ▶ Under these assumptions, the documents generated by the authors are likely relevant to the user's information need.

Language Model

- ▶ Let w be a symbol.
- ▶ A language *L* is defined as a set of symbol

$$L=\{w_1,\ldots,w_N\}$$

- A Language Model (LM) is a language L provided with a probability function
- Example:

- Remove stopwords and stem words to obtain bench goat live bench goat dies
- ► Language is *L* = {bench, goat, live, die} such that

$$P(\mathsf{bench}) = \frac{2}{6}$$
 $P(\mathsf{goat}) = \frac{2}{6}$ $P(\mathsf{live}) = \frac{1}{6}$ $P(\mathsf{die}) = \frac{1}{6}$

QLM

- Mostly used in IR.
- Queries are LMs.
- Documents are samples.
- ▶ The IRS looks for the most likely document given a query:

$$B^* = \arg_B \max P(B \mid Q)$$

where Q is the Query Language Model (QLM) and B is a document event.

▶ Documents are ranked by $P(B \mid Q)$.

How to estimate a QLM

- ► However, *Q* is not completely known: the language is known but the probability is unknown.
- Bayes' theorem:

$$P(B \mid Q) = \frac{P(Q \mid B)P(B)}{P(Q)}$$

- \triangleright P(Q) is constant.
- \triangleright P(B) uniform or estimated by external sources.
- ► Estimation: B is an n-gram $w_{(1)} \dots w_{(n)}$

$$P(Q|B) = p_B(w_{(1)})p_B(w_{(2)}|w_{(1)})\cdots p_B(w_{(n)}|w_{(n-1)}\cdots w_{(1)})$$

► Stochastic independence:

$$P(Q|B) = p_B(w_{(1)}) \cdots p_B(w_{(n)})$$

where

$$p_B(w_{(i)}) = \frac{f(w_{(i)}, B)}{\sum_{i=1}^n f(w_{(i)}, B)}$$

and f(w, B) is the frequency of $w_{(j)}$ in $B = \{0, 0, 0\}$ is the frequency of $w_{(j)}$ in $B = \{0, 0, 0\}$ in $A = \{0, 0, 0\}$ is the frequency of $A = \{0, 0, 0\}$ in $A = \{0, 0, 0\}$ in $A = \{0, 0, 0\}$ is the frequency of $A = \{0, 0, 0\}$ in $A = \{0, 0\}$ in $A = \{0, 0, 0\}$ in $A = \{0, 0, 0\}$ in $A = \{0, 0, 0\}$ in $A = \{0, 0\}$ in $A = \{0, 0, 0\}$ in A

Mixture and smoothing

- ▶ Problem: f(w, B) might be 0.
- Solution: mixture.


$$\hat{p}_B(w_{(i)}) = (1 - \lambda) \frac{f(w_{(i)}, B)}{\sum_{i=1}^n f(w_{(i)}, B)} + \lambda \frac{f(w_{(i)}, V)}{\sum_{i=1}^n f(w_{(i)}, V)}$$

where ${\cal V}$ is the collection language.


Alternatively, smoothing.

$$\hat{p}_B(w_{(i)}) = \frac{f(w_{(i)}, B) + a}{\sum_{w \in B} f(w_{(i)}, B) + a + b}$$

Mixture



Smoothing



Summary

Information Retrieval Modeling

Towards modeling Boolean Modeling Vector Space Modeling Relevance Modeling Language Modeling

Evaluation

Setting

- ► Topic set: TREC-6, TREC-7, TREC-8.
- ▶ Mean Average Precision (AP) (MAP) presented by:
- Query type: topic title-only, topic title and description.
- Model: LM, BM25, VSM-TFIDF.
- RF: without Pseudo Relevance Feedback (PRF), with PRF (i.e. no explicit RF).
- ▶ When with PRF: N. PRF documents, N. PRF terms = $\{5,10\}$ × $\{5,10\}$.
- ▶ Note that the number of PRF terms and the number of PRF documents are free parameters.

Some general comments

- ▶ Long queries are not worse (usually better) than short queries.
- ▶ RF improves TFIDF and BM25 and does not improve LM.
- ▶ RF improves effectiveness with a few documents and terms (n = 5, k = 5); larger numbers do not provide further increment.
- LM seems slightly superior to TFIDF and BM25 when RF is not applied, but...
- ► The experiments have been performed using Lemur, which is the IRS developed by a LM research group.

Detailed results follow

- Topic title-only queries.
- N. PRF documents: 5.
- N. PRF terms: 5.
- ► TREC-6 topic set.

	0.1402
PRF	0.1424
	0.1129
PRF	0.1424
	0.1302
PRF	0.1424
	PRF

- Topic title-only queries.
- N. PRF documents: 5.
- N. PRF terms: 5.
- ► TREC-7 topic set.

LM		0.1807
LM	PRF	0.1800
BM25		0.1549
BM25	PRF	0.1800
VSM-TFIDF		0.1687
VSM-TFIDF	PRF	0.1800

- Topic title-only queries.
- N. PRF documents: 5.
- N. PRF terms: 5.
- ► TREC-8 topic set.

	0.1708
PRF	0.1682
	0.1582
PRF	0.1751
	0.1588
PRF	0.1747
	PRF

- ► Topic title and description queries.
- N. PRF documents: 5.
- N. PRF terms: 5.
- ► TREC-6 topic set.

	0.1582
PRF	0.1516
	0.1377
PRF	0.1516
	0.1743
PRF	0.1516
	PRF

- ► Topic title and description queries.
- N. PRF documents: 5.
- N. PRF terms: 5.
- ► TREC-7 topic set.

LM		0.1773
LM	PRF	0.1759
BM25		0.1427
BM25	PRF	0.1759
VSM-TFIDF		0.1818
VSM-TFIDF	PRF	0.1759

- ► Topic title and description queries.
- N. PRF documents: 5.
- N. PRF terms: 5.
- ► TREC-8 topic set.

	0.1498
PRF	0.1499
	0.1351
PRF	0.1418
	0.1594
PRF	0.1602
	PRF

- Topic title-only queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 5.
- ► TREC-6 topic set.

LM		0.1402
LM	PRF	0.1403
BM25		0.1129
BM25	PRF	0.1204
VSM-TFIDF		0.1302
VSM-TFIDF	PRF	0.1276

- Topic title-only queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 5.
- ► TREC-7 topic set.

LM		0.1807
LM	PRF	0.1804
BM25		0.1549
BM25	PRF	0.2032
VSM-TFIDF		0.1687
VSM-TFIDF	PRF	0.1940

- Topic title-only queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 5.
- ► TREC-8 topic set.

LM		0.1708
LM	PRF	0.1680
BM25		0.1582
BM25	PRF	0.1773
VSM-TFIDF		0.1588
VSM-TFIDF	PRF	0.1715

- ► Topic title and description queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 5.
- ► TREC-6 topic set.

	0.1582
PRF	0.1454
	0.1377
PRF	0.1727
	0.1743
PRF	0.1812
	PRF

- ► Topic title and description queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 5.
- ► TREC-7 topic set.

LM		0.1773
LM	PRF	0.1751
BM25		0.1427
BM25	PRF	0.1955
VSM-TFIDF		0.1818
VSM-TFIDF	PRF	0.2005

- ► Topic title and description queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 5.
- ► TREC-8 topic set.

LM		0.1498
LM	PRF	0.1503
BM25		0.1351
BM25	PRF	0.1407
VSM-TFIDF		0.1594
VSM-TFIDF	PRF	0.1594

- Topic title-only queries.
- ▶ N. PRF documents: 10.
- ▶ N. PRF terms: 10.
- ► TREC-6 topic set.

	0.1402
PRF	0.1426
	0.1129
PRF	0.1205
	0.1302
PRF	0.1297
	PRF

- Topic title-only queries.
- ▶ N. PRF documents: 10.
- ▶ N. PRF terms: 10.
- ► TREC-7 topic set.

LM		0.1807
LM	PRF	0.1854
BM25		0.1549
BM25	PRF	0.2150
VSM-TFIDF		0.1687
VSM-TFIDF	PRF	0.2028

- Topic title-only queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 10.
- ► TREC-8 topic set.

LM		0.1708
LM	PRF	0.1743
BM25		0.1582
BM25	PRF	0.1880
VSM-TFIDF		0.1588
VSM-TFIDF	PRF	0.1843

- ► Topic title and description queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 10.
- ► TREC-6 topic set.

LM		0.1582
LM	PRF	0.1517
BM25		0.1377
BM25	PRF	0.1773
VSM-TFIDF		0.1743
VSM-TFIDF	PRF	0.1866

- ► Topic title and description queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 10.
- ► TREC-7 topic set.

LM		0.1773
LM	PRF	0.1915
BM25		0.1427
BM25	PRF	0.1997
VSM-TFIDF		0.1818
VSM-TFIDF	PRF	0.2077

- ► Topic title and description queries.
- ▶ N. PRF documents: 10.
- N. PRF terms: 10.
- ► TREC-8 topic set.

	0.1498
PRF	0.1436
	0.1351
PRF	0.1405
	0.1594
PRF	0.1603
	PRF

An Investigation of the laws of Thought. Walton and Maberly, 1854.

probabilistic information retrieval.

A. V. Aho and J. D. Ullman.

[3] W. Cooper. Getting beyond Boole.

Information Processing & Management, 24:243–248, 1988.

W. Cooper. [4] Some inconsistencies and misidentified modeling assumptions in

[5]

/Information Retrieval Modeling/Evaluation/

G. Boole.

[2]

ACM Transactions on Information Systems, 13(1):100–111, Jan. 1995.

W. Croft and D. Harper.

Journal of Documentation, 35:285–295, 1979.

[6] W. Croft and J. Lafferty, editors. Massimo Melucci/84/ML School, 2015

Using probabilistic models of document retrieval without relevance information.

The Art of Computer Programming, volume 1-4.

Addison-Wesley Professional, III edition, 2011.

Probabilistic relevance models based on document and query generation,

Language Modeling for Information Retrieval, volume 13 of Kluwer

International Series on Information Retrieval.

Kluwer Academic Publishers, 2002.

Volume 13 of Croft and Lafferty [6], 2002.

J. Lafferty and C. Zhai.

/Information Retrieval Modeling/Evaluation/

D. E. Knuth.

chapter 1.

[7]

[8]

[9] V. Lavrenko and W. Croft.

Relevance-based language models.

In *Proceedings of SIGIR*, pages 120–127, New Orleans, LO, USA, Sept. 2001.

[10] M. Maron and J. Kuhns.
On relevance, probabilistic indexing and retrieval.

Journal of the ACM, 7:216–244, 1960.

[11] M. Melucci.

The boolean model. Encyclopedia on Database Systems, 2009.

[12] M. Melucci. The vector space model.

Encyclopedia on Database Systems, 2009.

[13] J. Ponte and W. Croft. A language modeling approach to information retrieval.

In Proceedings of SIGIR, pages 275–281. ACM Press, Aug. 1998.

[14] S. Robertson. The probability ranking principle in information retrieval.

Journal of Documentation, 33(4):294-304, 1977.

[15] S. Robertson and S. Walker.

/Information Retrieval Modeling/Evaluation/

Some simple effective approximations to the 2-Poisson model for probabilistic weighted retrieval.

In Proceedings of SIGIR, pages 232–241, 1994.

[16] S. Robertson and H. Zaragoza. The probabilistic relevance framework: BM25 and beyond.

Relevance feedback in information retrieval.

Prentice-Hall, Englewood Cliffs, NJ, 1971.

Automatic Information Organization and Retrieval.

In G. Salton, editor, *The SMART Retrieval System: Experiments in Automatic Document Processing*, chapter 14, pages 313–323.

[19] G. Salton.

A theory of indexing.

[17] J. Rocchio.

[18] G. Salton.

A theory of Indexing.

Philadelphia: Society for Industrial and Applied Mathematics, 1975.

[20] G. Salton.

Mc Graw Hill, New York, NY, 1968.

Mathematics and information retrieval.

Journal of Documentation, 35(1):1–29, 1979.

[21] G. Salton.

Automatic Text Processing.

Addison-Wesley, 1989.

[22] G. Salton and C. Buckley.

Massimo Melucci/87/ML School, 2015

Term weighting approaches in automatic text retrieval. Information Processing & Management, 24(5):513–523, 1988. [23] G. Salton and C. Buckley.

Journal of the American Society for Information Science, 41(4):288–297,

Technical Report TR83-539, Cornell University, Computer Science

Improving retrieval performance by relevance feedback.

[24] G. Salton, E. A. Fox, C. Buckley, and E. M. Voorhees. Boolean guery formulation with relevance feedback.

Department, Jan. 1983. [25] G. Salton and M. McGill.

/Information Retrieval Modeling/Evaluation/

1990.

Introduction to Modern Information Retrieval.

McGraw-Hill, New York, NY, 1983.

- [26] G. Salton, A. Wong, and C. Yang.
- A vector space model for automatic indexing. Communications of the ACM, 18(11):613-620, 1975.
- [27] A. Singhal, C. Buckley, and M. Mitra.
- Pivoted document length normalization.
 - In Proceedings of SIGIR, pages 21–29, 1996. Massimo Melucci/88/ML School, 2015

[28] K. Sparck Jones.

[31] C. J. Van Rijsbergen.

- Search term relevance weighting given little relevance information. Journal of Documentation, 35:30–48, 1979.
- [29] K. Sparck Jones and P. Willett.
 - Readings in Information Retrieval.
 - Morgan Kaufmann, San Francisco, CA, 1997.
- [30] H. Turtle and J. Flood.
 - Query evaluation: strategies and optimizations.
 - Inf. Process. Manage., 31(6):831-850, Nov. 1995.
- - Information Retrieval.
 - Butterworths, London, second edition, 1979.
- [32] C. J. van Rijsbergen.
- A non-classical logic for Information Retrieval.
 - The Computer Journal, 29(6):481-485, 1986.
 - [33] C. Zhai.
 - Statistical Language Models for Information Retrieval: A Critical Reviews Massimo Melucci/89/ML School, 2015

Foundations and Trends in Information Retrieval. Now Publishers Inc., 2008.

[34] C. Zhai and J. Lafferty.

Model-based feedback in the language modeling approach to information retrieval.

In *Proceedings of CIKM*, pages 403–410, Atlanta, GA, USA, Nov. 2001.

[35] C. Zhai and J. Lafferty.

A study of smoothing methods for language models applied to ad-hoc information retrieval.

In Proceedings of SIGIR, pages 334–342, New Orleans, LA, USA, Sept. 2001.